




LED Fully Illuminated Bulb(6W)



Dimension:



Specification

Model No.	LOM-A19CS6F8	LOM-A19WS6F8
Input Voltage	AC 110/220 V	AC 110/220 V
Rated Power	6W $\pm$ 10%	6W $\pm$ 10%
Total Lumens	720 lm	600 lm
Lumens Efficiency	120 lm/W	100 lm/W
Color Temp.	5800~6300 K	2700~3000 K
CRI	80	80
Power Factor	>0.5	>0.5
Base	E27	E27
Beam Angle(10%)	360°	360°
Operating Temp.	-25°C~40°C	-25°C~40°C
Life time	$\geq$ 30000 hrs	$\geq$ 30000 hrs
Dimensions	ϕ 59 X 110 mm	ϕ 59 X 110 mm
Weight	60 $\pm$ 20 g	60 $\pm$ 20 g




Remarks

- 1.The tolerance of luminous flux is $\pm$ 10%.
2. The dimension tolerance is $\pm$ 5mm.
- 3.Laster Tech Corporation LTD. All rights reserved. Product specifications are subject to change without notice.

Laster Tech Corporation LTD. Building F No.4,Minxiang St., Zhonghe City, Taipei County 235, Taiwan V1.1

www.sweeo.com TEL:+886-2-22226112 FAX:+886-2-22226196


LUMINOUS INTENSITY DISTRIBUTION



PACKAGE DRAWING

Dimensions :

Box :68*68*120mm,



Carton:520*325*325mm

Package: one bulb in an inner box, one master carton contain 100 inner boxes.

