




LED Plug-in Lamp



Dimension:



Specification


Model No.	LOM-PLC03F7-E27G23/G24	LOM-PLN03F7-E27G23/G24	LOM-PLW03F7-E27/G23/G24
Input Voltage	AC100-240V	AC100-240V	AC100-240V
Rated Power	3 W±10%	3W±10%	3W±10%
Total Lumens	330 lm	300 lm	300 lm
Lumens Efficiency	110 lm/W	100 lm/W	100 lm/W
Color Temp.	5800~6300K	4000~4500K	2700 ~3200K
CRI	>70	>70	>70
Operating Temp.	-25°C~40°C	-25°C~40°C	-25°C~40°C
Base	E27/G23/G24	E/27G23/G24	E27G23/G24
Life Time	≥ 30000 hrs	≥ 30000 hrs	≥ 30000 hrs
Beam angle	120°	120°	120°
Dimensions	E27:35 *155 ,G23/G24:35*150 mm	E27:35 *155 ,G23/G24:35*150 mm	E27:35 *155 ,G23/G24:35*150 mm
Weight	40±15 g	40±15 g	40±15 g

Remarks

- 1.The tolerance of luminous flux is ±10%.
2. The dimension tolerance is ±5mm.
- 3.Laster Tech Corporation LTD. All rights reserved. Product specifications are subject to change without notice.


Distribution Curves /Illuminance

Distribution Curves:




Illuminance:

Cool White/Neutral White



Warm White



Installation

- Switch off electricity
- Remove the compact florescent lamp
- Cut off the ballast
- Pull in the led plug-in lamp